

DATA SHEET


VARIAIR SV 201/2 **SIDE CHANNEL** **VACUUM PUMPS**

double stage, air-cooled
frequency inverter


MAKE IT BECKER.






figure VARIAIR SV 300



- 1 Vacuum connection (G2)
- 2 Pressure connection (G2)
- 3 Rubber buffer position (optional)
- 4 Optional with shorter silencers
- * Device dimensions without pedestal (optional) under the silencer
- Dimensions in mm [inch]

Suction air rate	Vacuum relative	Frequency	Emission sound pressure level ¹⁾	Weight	 Frequency inverter VAU4/4	 A
m ³ /h max.	mbar max.	Hz	dB(A) @ -290 mbar (67 Hz)	kg	4.0 kW 400–480 V ±10% 50/60 Hz	max.
175	-420	10–100	73.5	32		16

¹⁾ According to DIN EN ISO 11203, accuracy class of measurement: class 2, extended measurement uncertainty: 3 dB
1 m [39.4 inch] distance, at medium load, both connection sides piped



Reference data (atmosphere): 1000 mbar (100 kPa), 20°C (68°F)

Tolerance: $\pm 10\%$

Max. ambient temperature: -10°C ... 40°C (14°F ... 104°F)



MAKE IT BECKER.